PVC Strip Curtains

Flexible PVC strips hung as a curtain across doorways to hold back air, dust, noise and insects while people, trolleys and forklifts pass through. Supplied from our Dammam warehouse as full rolls, cut strips or complete door kits with rail and hardware.



Installed at a warehouse door, Saudi Arabia



Clear rolls in stock, Dammam



Polar roll, 2 mm x 200 mm x 50 m

STRIP GRADES

Grade	Typical sizes (width x thickness)	Typical temperature	Typical use
Standard clear	200 x 2, 300 x 3, 400 x 4 mm; 50 m rolls	About -15 to +50 °C	Warehouse doors, workshops, loading bays
Double-ribbed	As standard clear; wider and thicker for heavy traffic	Ambient grade	Forklift doorways, dock doors
Polar / freezer	300 x 3 or 400 x 4 mm typical; 2 x 200 mm rolls also stocked	Down to about -25 °C	Cold rooms, chillers, freezers, reefer vehicles
Welding screen	Red or green tint; cut to bay size	Ambient grade	Welding bays, fabrication shops
Anti-insect (yellow)	200 x 2, 300 x 3 mm typical	Ambient grade	Food areas, kitchens, doors to open ground
Magnetic door curtain	300 x 3 mm; 30 m roll	Ambient grade	Dust control, tight-seal doorways

KEY FEATURES

- Clear, flexible PVC that keeps visibility for drivers and pedestrians
- Individual strips can be replaced without removing the whole curtain
- Reduces air exchange to help hold temperature in cold rooms and cut energy use
- Rail, hook-on or bolt-on clamps and cut-to-size strips available

Not for freezers: standard PVC stiffens and can crack in sub-zero rooms. Use polar grade and tell us your real operating temperature. Strip curtains reduce, but do not stop, air exchange and are not fire-rated doors, machine guards or certified safety barriers.

Sizing, fitting and supply

SIZES, THICKNESS AND OVERLAP

Width x thickness	Best for	Typical door
200 x 2 mm	Pedestrian and small doorways	Up to about 2.5 m high
300 x 3 mm	Standard warehouse and cold-room doors; trolley and pallet-truck traffic	Most general doors
400 x 4 mm	Large dock and forklift doors; higher wind or pressure differences	Large openings

Rolls are typically 50 m, or strips are cut to door height. Other widths and thicknesses are available on request. Exact dimensions, grades and tolerances are confirmed on your quotation.

COUNTING THE STRIPS

Strips = opening width / (strip width - overlap), rounded up

Example: 2.5 m door, 300 mm strips, 50% overlap: 2,500 / 150 = 16.7, so **17 strips**. Use about 50% overlap for cold stores and freezers; 25% can suit ambient doors.

FITTING

- Measure the clear width and the height from the rail to the floor; strip length is the height minus a floor gap of about 10 mm
- Fit the rail above the opening and hang the strips with overlap along the full width
- Keep the bottom edge just clear of the floor so strips do not drag or bunch

CARE

When	What to do
Regularly	Wipe clean with mild soap and water; clear debris from the bottom edge
Every few weeks	Inspect for cracks, yellowing, sharp edges, loss of flexibility, loose clamps
When damaged	Replace the single strip before a larger gap forms

SUPPLY AND DOCUMENTS

- Stock held in Dammam; typical dispatch 1-3 working days, with delivery across Saudi Arabia and the GCC
- Material Test Certificate (MTC) supplied with every order
- Supplied as full rolls, cut strips or complete kits with rail and hardware
- To quote: send door width and height, environment and temperature, traffic type and delivery city

DIODE TRADING EST
Sammam Althunai Commercial Establishment | CR 2051245534 | VAT 300541061800003
Warehouse: Al Khalidiyah Ash Shamaliyah, Dammam 32231, Saudi Arabia
sales@diode.sa | +966 51 083 8213 | www.diode.sa/product/pvc-strip-curtains/

Values are typical and for guidance only. Final selection depends on temperature, traffic, hygiene and site conditions; dimensions, grades and tolerances are confirmed on your quotation.